



MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS

PRODUCT NAME: CARBONYL SULFIDE (0 – 5% vol.) IN NITROGEN

MSDS NO: 103

Version: 1

Date: January 2006

1. Chemical Product and Company Identification

Gasco Affiliates, LLC
1933 Whitfield Park Loop
Sarasota, FL 34243

TELEPHONE NUMBER: (941) 755-8806
FAX NUMBER: (941) 755-8920
E-MAIL: info@gascogas.com

24-HOUR EMERGENCY NUMBER: 1-800-424-9300

PRODUCT NAME: CARBONYL SULFIDE (0 – 5% vol.) IN NITROGEN
CHEMICAL NAME: Carbonyl Sulfide in Nitrogen
COMMON NAMES/ SYNONYMS: None
TDG (Canada) CLASSIFICATION: 2.2
WHIMIS CLASSIFICATION: A

2. COMPOSITION/ INFORMATION ON INGREDIENTS

Table with 5 columns: INGREDIENT, %VOLUME, PEL-OSHA, TLV-ACGIH, LD50 or LC50 Route/Species. Rows include Carbonyl Sulfide and Nitrogen.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product is a colorless gas, which has a rotten-egg odor which may cause eye, skin and respiratory irritation. This product contains carbonyl sulfide, which in sufficient concentrations can cause acute respiratory failure and death.

ROUTE OF ENTRY:

Table showing health effects for Skin Contact, Skin Absorption, Eye Contact, Inhalation, Ingestion, Exposure Limits, Irritant, Sensitization, Reproductive Hazard, and Mutagen.

Carcinogenicity: --NTP: No IARC: No OSHA: No

EYE EFFECTS:

Contact may cause eye irritation with associated redness, swelling, and tears.



## MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS

**PRODUCT NAME: CARBONYL SULFIDE (0 – 5% vol.) IN NITROGEN**

### SKIN EFFECTS:

Contact may cause skin irritation.

### INGESTION EFFECTS:

Ingestion unlikely. Gas at room temperature.

### INHALATION EFFECTS:

Release of sufficient quantities may cause asphyxiation or suffocation by displacing oxygen content in the air. Symptoms of asphyxiation may begin with decreased night vision followed by decreased alertness, air hunger, fatigue, dizziness, headache, and decreased coordination. Carbonyl sulfide is hydrolyzed by water to carbon dioxide and hydrogen sulfide. Exposure to greater than 500 ppm hydrogen sulfide can result in respiratory paralysis and death within 30 to 60 minutes. Concentrations of 0.1 volume percent carbonyl sulfide and higher produce death in 2 hours or less.

### MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Individuals with impaired pulmonary function may be at increased risk from exposure.

### NFPA HAZARD CODES

Health: 2  
Flammability: 0  
Reactivity: 1

### HMIS HAZARD CODES

Health: 2  
Flammability: 0  
Reactivity: 1

### RATING SYSTEM

0= No Hazard  
1= Slight Hazard  
2= Moderate Hazard  
3= Serious Hazard  
4= Severe Hazard

---

## 4. FIRST AID MEASURES

### EYES:

PERSONS WITH POTENTIAL EXPOSURE SHOULD NOT WEAR CONTACT LENSES. Flush contaminated eyes with copious quantities of water. Part eyelids to assure complete flushing. Continue for a minimum of 15 minutes. Seek immediate medical attention.

### SKIN:

Remove contaminated clothing as rapidly as possible. Flush affected area with copious quantities of water. Seek immediate medical attention.

### INGESTION:

Not required

### INHALATION:

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED THE SELF-CONTAINED BREATHING APPARATUS. Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. If breathing has stopped administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

---

## 5. FIRE-FIGHTING MEASURES

These containers hold gas under pressure, with no liquid phase. If involved in a major fire, they should be sprayed with water to avoid pressure increases, otherwise pressures will rise and ultimately they may distort or burst to release the contents. The gases will not add significantly to the fire, but containers or fragments may be projected considerable distances - thereby hampering fire fighting efforts.

---



## MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS

**PRODUCT NAME: CARBONYL SULFIDE (0 – 5% vol.) IN NITROGEN**

### 6. ACCIDENTAL RELEASE MEASURES

In terms of weight, these containers hold very little contents, such that any accidental release by puncturing etc. will be of no practical concern.

---

### 7. HANDLING AND STORAGE

Suck back of water into the container must be prevented. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Use only in well-ventilated areas. Do not heat cylinder by any means to increase rate of product from the cylinder. Do not allow the temperature where cylinders are stored to exceed 130°F (54°C).

---

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Use adequate ventilation for extended use of gas.

---

### 9. PHYSICAL AND CHEMICAL PROPERTIES

PARAMETER:	VALUE:
Physical state	: Gas
Evaporation point	: N/A
pH	: N/A
Odor and appearance	: Colorless gas with a typical sulfide odor

---

### 10. STABILITY AND REACTIVITY

Stable under normal conditions. Expected shelf life 12 months.

---

### 11. TOXICOLOGICAL INFORMATION

Due to the small amount of gas in this cylinder, Toxicological effects are not expected to occur.

---

### 12. ECOLOGICAL INFORMATION

Due to the small amount of gas in this cylinder, ecological effects are not expected to occur.

---

### 13. DISPOSAL INFORMATION

Do not discharge into any place where its accumulation could be dangerous. Used containers are acceptable for disposal in the normal waste stream as long as the cylinder is empty and valve removed or cylinder wall is punctured; but GASCO encourages the consumer to return cylinders.

---



## MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS

**PRODUCT NAME: CARBONYL SULFIDE (0 – 5% vol.) IN NITROGEN**

### 14. TRANSPORT INFORMATION

	<u>United States DOT</u>	<u>Canada TDG</u>
<b>PROPER SHIPPING NAME:</b>	Compressed Gas N.O.S. (Carbonyl Sulfide in Nitrogen)	Compressed Gas N.O.S. (Carbonyl Sulfide in Nitrogen)
<b>HAZARD CLASS:</b>	2.2	2.2
<b>IDENTIFICATION NUMBER:</b>	UN1956	UN1956
<b>SHIPPING LABEL:</b>	NONFLAMMABLE GAS	NONFLAMMABLE GAS

---

### 15. REGULATORY INFORMATION

Carbonyl Sulfide is listed under the accident prevention provisions of section 112(r) of the Clean Air Act (CAA) with a threshold quantity (TQ) of 10,000 pounds.

---

### 16. OTHER INFORMATION

This MSDS has been prepared in accordance with the Chemicals (Hazard Information and Packaging for Supply (Amendment) Regulation 1996. The information is based on the best knowledge of GASCO, and its advisors and is given in good faith, but we cannot guarantee its accuracy, reliability or completeness and therefore disclaim any liability for loss or damage arising out of use of this data. Since conditions of use are outside the control of the Company and its advisors we disclaim any liability for loss or damage when the product is used for other purposes than it is intended.

MSDS/S010/106/January 2006